



## I Product Overview

<b>Thread</b>	Metric (M), PG, G, NPT
<b>Material</b>	Nickel Plated Brass Claw : PA66 (Nylon) UL94-V2 Hermetic Seal and O-Ring : NBR, Silicone Rubber
<b>Approvals</b>	CE, RoHS, REACH
<b>Temperature</b>	-40°C to 100°C, Short Time 120°C
<b>Protection Degree</b>	IP68
<b>Features</b>	EMC cable gland is designed for use with unarmoured, elastometric and plastic cable or braided cables where EMC is required. Suitable for both indoor & outdoor applications. seals on cable outer sheath to IP68, and if fitted with patented EMC membrane, suitable to carry on cable shield.



 **RoHS CE REACH IP68**

Product Model	ITEM				Range Ø	GL Thread Length	H Joint Length	Spanner Size
	M	PG	G	NPT				
<b>TPE-EMC</b> - *ITEM*	M12x1.5	PG7	1/4"	1/4"	3 - 6.5 4 - 8	6.5 8.0	21 21	14 17/14
	M16x1.5	PG9			3 - 6 4 - 8	8.0 8.0	25 25	18 18
	M18x1.5	PG11	3/8"	3/8"	5 - 10	8.0	25	20/18 20
	M20x1.5	PG13.5	1/2"	1/2"	6 - 12 10 - 14	8.0 8.0	29 29	22 24/22
	M22x1.5	PG16			10 - 14	8.0	29	24
	M25x1.5	PG21	3/4"	3/4"	10 - 14	9.0	30	24/27
					12 - 16	9.0	30	27
					13 - 18	9.0	30	30/27
	M32x1.5	PG29	1"	1"	15 - 22 18 - 25	10.0 10.0	32 32	35 40/35
	M40x1.5	PG36	1-1/4"	1-1/4"	18 - 25 22 - 30	11.0 11.0	35 35	40/45 45
	M50x1.5				PG42	1-1/2"	1-1/2"	25 - 33
					32 - 38	13.0	39	57/55
	M63x1.5	PG48	2"	2"	37 - 44 42 - 52	14.0 14.0	40 40	64/68 78/68

