

Product Overview : Flexible Metal Overbraided SUS304

Material	Metal / Stainless Steel 304
Temperature	-50°C to 300°C
Protection Degree	IP40
Style	Squarelocked
Features	Most suitable for use in Hazardous location industrial environments and high temperature such as welding machines and meta casting machines. Also for industrial environments where higher abrasion resistance or screening are required.



Product Model	Flexible Size	Inner Size	Outer Size	Bend Radius	Qty/Bag (m.)
SB007	1/4"	8.5	11.45	60.0	100
SB008	5/16"	10.5	14.15	70.0	50
SB010	3/8"	12.5	16.45	70.0	50
SB011	1/2"	16.0	20.65	90.0	50
SB012	3/4"	20.0	25.45	110.0	50
SB013	1"	25.0	31.15	150.0	50
SB014	1-1/4"	32.5	38.65	175.0	25
SB015	1-1/2"	38.5	45.65	200.0	25
SB016	2"	50.5	59.45	230.0	20
SB017	2-1/2"	65.0	73.65	250.0	10
SB018	3"	76.0	84.65	300.0	10
SB019	4"	103.0	109.65	500.0	5

Product Overview : Flexible Metal Overbraided SUS304 Coat PVC

Material	Metal / Stainless Steel 304 / PVC
Temperature	-20°C to 90°C
Protection Degree	IP65
Style	Squarelocked
Features	Suitable for use in hazardous location industrial environments where higher abrasion resistant suitable for use in hazardous locations industrial environments where higher abrasion resistant.



Product Model	Flexible Size	Inner Size	Outer Size	Bend Radius	Qty/Bag (m.)
SBP007	1/4"	8.5	12.95	60.0	100
SBP008	5/16"	10.5	14.95	70.0	50
SBP010	3/8"	12.5	17.45	70.0	50
SBP011	1/2"	16.0	21.45	90.0	50
SBP012	3/4"	20.0	26.25	110.0	50
SBP013	1"	25.0	31.85	150.0	50
SBP014	1-1/4"	32.5	39.65	175.0	25
SBP015	1-1/2"	38.5	46.85	200.0	25
SBP016	2"	50.5	59.95	230.0	20
SBP017	2-1/2"	65.0	74.65	250.0	10
SBP018	3"	76.0	85.85	300.0	10
SBP019	4"	103.0	111.15	500.0	5