


Product Overview : Metal Fitting Liquid Tight - Zinc Alloy

Material	Metal Zinc Alloy
Temperature	-20°C to 90°C
Protection Degree	IP67
Style	Straight / Angle 90 / Angle 45
Features	For use with Metallic tight conduits and non-metallic liquid tight.



Thread Type	Product Model			Conduit (IN)	Thread	MM		Qty/Bag
	Straight	Angle 90	Angle 45			A	B	
G	LTCD-G06			3/16"	G1/4"	8.5	12.8	100
	LTCD-G07			1/4"	G3/8"	11.0	15.9	100
	LTCD-G08			5/16"	G3/8"	11.0	15.9	100
	LTCD-G09	LTCD-G209	LTCD-G309	3/8"	G3/8"	10.0	16.2	100
	LTCD-G10	LTCD-G20	LTCD-G30	3/8"	G1/2"	8.8	20.3	100
	LTCD-G11	LTCD-G21	LTCD-G31	1/2"	G1/2"	11.0	20.3	100
	LTCD-G12	LTCD-G22	LTCD-G32	3/4"	G3/4"	13.0	25.9	50
	LTCD-G13	LTCD-G23	LTCD-G33	1"	G1"	13.5	32.6	50
	LTCD-G14	LTCD-G24	LTCD-G34	1-1/4"	G1-1/4"	15.5	41.3	20
	LTCD-G15	LTCD-G25	LTCD-G35	1-1/2"	G1-1/2"	17.2	47.4	20
	LTCD-G16	LTCD-G26	LTCD-G36	2"	G2"	19.0	58.7	10
	LTCD-G17			2-1/2"	G2-1/2"	23.0	74.3	10
	LTCD-G18			3"	G3"	24.0	87.2	5

Thread Type	Product Model			Conduit (IN)	Thread	MM		Qty/Bag
	Straight	Angle 90	Angle 45			A	B	
M	LTCD-M06			3/16"	M14 x 1.5	8.0	13.4	100
	LTCD-M07			1/4"	M16 x 1.5	10.0	15.5	100
	LTCD-M08			5/16"	M16 x 1.5	8.2	15.0	100
	LTCD-M09	LTCD-M209		3/8"	M16 x 1.5	10.5	15.4	100
	LTCD-M10	LTCD-M20		3/8"	M20 x 1.5	10.8	19.4	100
	LTCD-M11	LTCD-M21		1/2"	M20 x 1.5	11.0	19.4	100
	LTCD-M12	LTCD-M22		3/4"	M25 x 1.5	12.0	24.4	50
	LTCD-M13	LTCD-M23		1"	M32 x 1.5	12.5	31.6	50
	LTCD-M14	LTCD-M24		1-1/4"	M40 x 1.5	15.0	39.4	20
	LTCD-M15	LTCD-M25		1-1/2"	M50 x 1.5	14.5	49.5	20
	LTCD-M16	LTCD-M26		2"	M63 x 1.5	18.5	62.5	10
	LTCD-M17			2-1/2"	M76 x 2.0	21.0	75.2	10
	LTCD-M18			3"	M88 x 2.0	24.0	87.3	5



บริษัทฯ ขอสงวนสิทธิ์การเปลี่ยนแปลงราคา โดยมิต้องแจ้งให้ทราบล่วงหน้า

ตัวแทนโปรดติดต่อฝ่ายขาย Tel 02-027-7841, 095-543-5665 / Fax 02-026-6529

Email : sales.tpetrading@gmail.com / ID Line : @tpetrading