



Stainless Steel End Style Straight Connector

Product Overview : Stainless Steel End Style Straight Connector

Material	Location A, C, F are made of 304 stainless steel, B. E are made of chemigums, and D is made of stainless steel
Thread	PG, G
Temperature	-40°C to 100°C, Instantaneously can be 120°C
Protection Degree	IP65
Colours	Metalic (White)
Features	Made of 304 stainless steel, nice looking, compact structure, strength higher than normal conduit connector. Ferrule design make conduit connection tightly, easy assembly, and strong pull resistance. Water resistant, dust resistant, inactive with salts, acid and alkali resistance, alcohols, oils and greases as well as general solvent. G style thread standard, others should be customized.



PG Type

Product Model	G	Metric	Thread Standard (PG)	Thread O.D (D1) mm	Thread Length (L1) mm.	SW (mm.)	Package Unit (Unit/Pack)
DPB-6-PG7	3/16"	φ 6	PG7	12.5	7	18/16	100
DPB-8-PG9	5/16"	φ 8	PG9	15.2	8	24/22	50
DPB-10-PG9	1/4"	φ 10	PG9	15.2	8	24/22	50
DPB-13-PG11/PG13.5	3/8"	φ 13	PG11/PG13.5	18.6/20.4	10	26	50
DPB-16-PG13.5/PG16	1/2"	φ 16	PG13.5/PG16	20.4/22.5	10	30	50
DPB-20-PG21	3/4"	φ 20	PG21	28.3	12	35	25
DPB-25-PG29	1"	φ 25	PG29	37	12	43	20
DPB-32-PG29	1 1/4"	φ 32	PG29	37	14	52	10
DPB-48-PG36/PG42	1 1/2"	φ 38	PG36/PG42	47/54	14	60	10
DPB-51-PG48	2"	φ 51	PG48	59.3	15	75	5

G Type

Product Model	G	Metric	Thread Standard (G)	Thread O.D (D1) mm	Thread Length (L1) mm.	SW (mm.)	Package Unit (Unit/Pack)
DPB-6-G1/4	3/16"	φ 6	G1/4"	13.2	7	18/16	100
DPB-8-G3/8	5/16"	φ 8	G3/8"	16.5	8	24/22	50
DPB-10-G3/8	1/4"	φ 10	G3/8"	16.5	8	24/22	50
DPB-13-G3/8	3/8"	φ 13	G3/8"	16.5	10	26	50
DPB-16-G1/2	1/2"	φ 16	G1/2"	21.3	10	30	50
DPB-20-G3/4	3/4"	φ 20	G3/4"	26.6	12	35	25
DPB-25-G1	1"	φ 25	G1"	33.4	12	43	20
DPB-32-G1-1/4	1-1/4"	φ 32	G1-1/4"	42.1	14	52	10
DPB-48-G1-1/2	1-1/2"	φ 38	G1-1/2"	47.8	14	60	10
DPB-51-G2	2"	φ 51	G2"	59.6	15	75	5
DPB-64-G2-1/2	2-1/2"	φ 64	G2-1/2"	75.1	20	89/87	2