

FOXI PREMIUM PUR L (FOOD GRADE)



Material	Highly abrasion resistant polyester polyurethane
Temperature	-40°C ~ 90°C, Short time to 125°C
Helix	Spring steel wire, copper coated.
Wall Thickness	0.75 mm.
Features	• Permanently anti-static with surface resistance of RO < 10 Ohm • For Food contact according to FDA21 CFR 177.1200 - 178.2010 Directive no 10/2011

PUR-L Series

ID (mm.)	Work Pressure (Bar)	Vacuum (Bar)	Bending Radius (mm.)	Outer-Ø ca. mm.	Weight (kg/m)	Length (m.)	Article No.
25	3.220	0.785	31	31	0.25	10/15/20	3218-025-101
32	2.520	0.711	40	40	0.35	10/15/20	3218-032-101
38	2.100	0.662	46	46	0.39	10/15/20	3218-038-101
40	2.100	0.662	48	48	0.40	10/15/20	3218-040-101
45	1.840	0.588	53	53	0.42	10/15/20	3218-045-101
50	1.680	0.515	58	58	0.45	10/15/20	3218-050-101
60	1.400	0.441	68	68	0.53	10/15/20	3218-060-101
65	1.260	0.368	73	73	0.64	10/15/20	3218-065-101
70	1.120	0.368	78	78	0.68	10/15/20	3218-070-101
75	1.120	0.294	84	84	0.72	10/15/20	3218-075-101
80	0.890	0.294	88	88	0.76	10/15/20	3218-080-101
90	0.840	0.221	99	99	0.88	10/15/20	3218-090-101
100	0.840	0.221	110	110	0.95	10/15/20	3218-100-101
110	0.700	0.221	119	119	1.03	10/15	3218-110-101
120	0.700	0.221	129	129	1.12	10/15	3218-120-101
125	0.700	0.221	135	135	1.18	10/15	3218-125-101
140	0.560	0.147	149	149	1.38	10/15	3218-140-101
150	0.560	0.147	161	161	1.48	10/15	3218-150-101
160	0.560	0.147	170	170	1.74	10/15	3218-160-101
175	0.420	0.147	185	185	1.85	10/15	3218-175-101
180	0.420	0.147	190	190	1.90	10/15	3218-180-101
200	0.420	0.147	214	214	2.30	10/15	3218-200-101
225	0.280	0.074	235	235	2.55	10/15	3218-225-101
250	0.280	0.074	260	260	3.02	10/15	3218-250-101
275	0.280	0.074	284	284	3.11	10	3218-275-101
300	0.280	0.066	310	310	3.20	10	3218-300-101