



I Product Overview



Thread	Metric (M), PG
Material	PA Nylon, UL 94V-2
Temperature	-40°C to 100°C, Short Time 120°C
Colours	Black (RAL9005) / White Gray (RAL9018)
Features	Close the hole that is not in use. Used to close to prevent dust or water against unused holes and equipment having close threads.
Accessories	Locknut, Sealing washer
Approvals	CE, RoHS

TPE-SC-PG7-BK = BK = Black

TPE-SC-PG7-LG = LG = LG



Thread Type	Product Model	Thread	AG (mm.)	GL (mm.)	Body Size	Spanner Size	Qty / Bag
PG	TPE-SC-PG7	PG7	12.5	8.5	12.5	15.0	100
	TPE-SC-PG9	PG9	15.2	8.5	13.0	19.0	100
	TPE-SC-PG11	PG11	18.6	9.0	13.0	22.0	100
	TPE-SC-PG13.5	PG13.5	20.4	9.0	13.0	25.0	100
	TPE-SC-PG16	PG16	22.5	10.5	15.0	27.0	100
	TPE-SC-PG21	PG21	28.3	10.5	15.5	33.0	100
	TPE-SC-PG29	PG29	37.0	11.5	16.0	44.0	50
	TPE-SC-PG36	PG36	47.0	13.5	18.0	55.0	50
	TPE-SC-PG42	PG42	54.0	13.5	18.5	62.0	20
	TPE-SC-PG48	PG48	59.3	14.5	19.5	68.0	20

Thread Type	Product Model	Thread	AG (mm.)	GL (mm.)	Body Size	Spanner Size	Qty / Bag
M	TPE-SC-M12x1.5	M12x1.5	12.0	8.5	12.5	15.0	100
	TPE-SC-M16x1.5	M16x1.5	16.0	8.5	13.0	19.0	100
	TPE-SC-M18x1.5	M18x1.5	18.0	9.0	13.0	22.0	100
	TPE-SC-M20x1.5	M20x1.5	20.0	9.0	13.0	25.0	100
	TPE-SC-M22x1.5	M22x1.5	22.0	10.5	15.0	27.0	100
	TPE-SC-M25x1.5	M25x1.5	25.0	10.5	15.5	29.0	100
	TPE-SC-M32x1.5	M32x1.5	32.0	10.5	16.0	38.0	50
	TPE-SC-M40x1.5	M40x1.5	40.0	11.5	18.0	46.0	50
	TPE-SC-M50x1.5	M50x1.5	50.0	13.5	18.0	56.0	20
	TPE-SC-M63x1.5	M63x1.5	63.0	14.0	19.0	68.0	20